

Contents

- [1 Introduction](#)
- [2 Assumption](#)
 - ◆ [2.1 Prerequisites](#)
 - ◆ [2.2 Allow for multicast traffic](#)
 - ◆ [2.3 Disable multicast traffic to reach the Wireless adapter](#)
 - ◆ [2.4 Setup an additional VLAN](#)
 - ◆ [2.5 Disable multicast traffic to reach the LAN Ports 1,2,3](#)
 - ◆ [2.6 Enable DHCP for the additional local Networks and final steps](#)
- [3 Block Multicast via Ebttables Firewall](#)

Introduction

This section explains how to use the DD-WRT GUI to configure DD-WRT supporting multicast IPTV traffic while at the same time enable some LAN ports and Wireless Clients working in parallel.

There are 2 ways to achieve this. The first is to unbridge the LAN area that shouldnt get flooded with mulicast packets. The second (and imho more elegand) way is to block mulicast traffic to the interfaces which doesnt need it.

Assumption

In the sample configuration, the TV media receiver is connected to LAN Port 4, and the router Ip is 192.168.1.1. Other configurations work accordingly.

Prerequisites

1. Ensure that you are at least on DD-WRT 24v1 Firmware, otherwise download the most recent release.
2. Connect the TV media receiver to Port 4. Connect other LAN connections to Ports 1,2,3

Allow for multicast traffic

1. Disable (uncheck) "Filter Multicast" on Security-->Firewall

Disable multicast traffic to reach the Wireless adapter

1. In Wireless-->Basic setting, set "Network Configuration" to "Unbridged", and "Multicast forwarding" to "disabled".
2. Provide 192.168.3.1 with subnet mask 255.255.255.0 as the IP address for Wireless connections

Setup an additional VLAN

1. In Setup-->VLANs, check the "tagged" checkboxes for Ports 1,2,3. Then, check the three accoring checkboxes in the VLAN 7 row, uncheck them in the VLAN 0 row, and finally uncheck the "tagged" checkboxes.
2. Apply the settings and reboot the router

Disable multicast traffic to reach the LAN Ports 1,2,3

1. In Setup-->Networking, check "Unbridged" for "Network Configuration vlan7", "Multicast forward" to "disable".
2. Below this entry, provide IP number 192.168.2.1 with subnet mask 255.255.255.0 as the IP address

Enable DHCP for the additional local Networks and final steps

1. In Setup-->Networking, add two DHCP Servers in the bottom area, one for vlan7, one for eth1 (keep the standard settign for the other fields)
2. Apply all changes, and reboot the router

Block Multicast via Ebttables Firewall

Leave the wifi brdged. Load the layer2 firewall modules and your ebttables rules via the firewall startup

```
insmod ebttables
insmod ebttable_filter
insmod ebt_pkttype
ebttables -A FORWARD -o "interface to block" --pkttype-type multicast -j DROP
ebttables -A OUTPUT -o "interface to block" --pkttype-type multicast -j DROP
```

If you want this script to run everytime your router starts, do the following:

- Go to **Administration->Commands**
- Paste commands in the **Commands window**
- Click **Save startup**

The drawback is ebttables will use sightly mode cpu time. Finally, enjoy TV, LAN, and Wireless simultaneously.